

Artificial Intelligence

Propositional logic

Propositional Logic: Syntax

- Syntax of propositional logic defines allowable sentences
- Atomic sentences consists of a single proposition symbol
 - Each symbol stands for proposition that can be True or False
- Symbols of propositional logic
 - Propositional symbols: P, Q, \dots
 - Logical constants: *True, False*
- Making complex sentences
 - Logical connectives of symbols: $\wedge, \vee, \Leftrightarrow, \Rightarrow, \neg$
 - Also have parentheses to enclose each sentence: (...)
- Sentences will be used for inference/problem-solving

Propositional Logic: Syntax

- $\text{True}, \text{False}, S_1, S_2, \dots$ are sentences
- If S is a sentence, $\neg S$ is a sentence
 - Not (negation)
- $S_1 \wedge S_2$ is a sentence, also $(S_1 \wedge S_2)$
 - And (conjunction)
- $S_1 \vee S_2$ is a sentence
 - Or (disjunction)
- $S_1 \Rightarrow S_2$ is a sentence
 - Implies (conditional)
- $S_1 \Leftrightarrow S_2$ is a sentence
 - Equivalence (biconditional)

Propositional Logic: Semantics

- Semantics defines the rules for determining the truth of a sentence (wrt a particular model)
- $\neg S$ is true iff S is false
- $S_1 \wedge S_2$ is true iff S_1 is true and S_2 is true
- $S_1 \vee S_2$ is true iff S_1 is true or S_2 is true
- $S_1 \Rightarrow S_2$ is true iff S_1 is false or S_2 is true
(is false iff S_1 is true and S_2 is false)
(if S_1 is true, then claiming that S_2 is true,
otherwise make no claim)
- $S_1 \Leftrightarrow S_2$ is true iff $S_1 \Rightarrow S_2$ is true and
 $S_2 \Rightarrow S_1$ is true (S_1 same as S_2)

Semantics in Truth Table Form

P	Q	$\neg P$	$P \wedge Q$	$P \vee Q$	$P \Rightarrow Q$	$P \Leftrightarrow Q$
False	False	True	False	False	True	True
False	True	True	False	True	True	False
True	False	False	False	True	False	False
True	True	False	True	True	True	True

Propositional Inference: Enumeration Method

- Truth tables can test for valid sentences
 - True under all possible interpretations in all possible worlds
- For a given sentence, make a truth table
 - Columns as the combinations of propositions in the sentence
 - Rows with all possible truth values for proposition symbols
- If sentence true in every row, then valid

Propositional Inference: Enumeration Method

- Test $((P \vee H) \wedge \neg H) \Rightarrow P$

P	H	$P \vee H$	$\neg H$	$(P \vee H) \wedge \neg H$	$((P \vee H) \wedge \neg H) \Rightarrow P$
False	False	False	True	False	True
False	True	True	False	False	True
True	False	True	True	True	True
True	True	True	False	False	True

Practice

- Test $(P \wedge H) \Rightarrow (P \vee \neg H)$

Simple Wumpus Knowledge Base

- For simplicity, only deal with the pits
- Choose vocabulary
 - Let $P_{i,j}$ be True if there is a pit in $[i,j]$
 - Let $B_{i,j}$ be True if there is a breeze in $[i,j]$
- KB sentences
 - FACT: “There is no pit in $[1,1]$ ”
 $R_1: \neg P_{1,1}$
 - RULE: “There is breeze in adjacent neighbor of pit”
 $R_2: B_{1,1} \Leftrightarrow (P_{1,2} \vee P_{2,1})$ *Need rule for*
 $R_3: B_{2,1} \Leftrightarrow (P_{1,1} \vee P_{2,2} \vee P_{3,1})$ *each square!*

Wumpus Environment

- Given knowledge base
- Include percepts as move through environment (online)
- Need to “deduce what to do”
- Derive chains of conclusions that lead to the desired goal
 - Use inference rules

$$\frac{\alpha}{\beta}$$

Inference rule: “ α derives β ”
Knowing α is true, then β must also be true

Inference Rules for Prop. Logic

- Modus Ponens
 - From implication and premise of implication, can infer conclusion

$$\frac{\alpha \Rightarrow \beta, \ \alpha}{\beta}$$

Inference Rules for Prop. Logic

- And-Elimination
 - From conjunction, can infer any of the conjuncts

$$\frac{\alpha_1 \wedge \alpha_2 \wedge \cdots \wedge \alpha_n}{\alpha_i}$$

Inference Rules for Prop. Logic

- And-Introduction
 - From list of sentences, can infer their conjunction

$$\frac{\alpha_1, \alpha_2, \dots, \alpha_n}{\alpha_1 \wedge \alpha_2 \wedge \dots \wedge \alpha_n}$$

Inference Rules for Prop. Logic

- Or-Introduction
 - From sentence, can infer its disjunction with anything else

$$\frac{\alpha_i}{\alpha_1 \vee \alpha_2 \vee \cdots \vee \alpha_n}$$

Inference Rules for Prop. Logic

- Double-Negation Elimination
 - From doubly negated sentence, can infer a positive sentence

$$\frac{\neg\neg\alpha}{\alpha}$$

Inference Rules for Prop. Logic

- Unit Resolution
 - From disjunction, if one of the disjuncts is false, can infer the other is true

$$\frac{\alpha \vee \beta, \quad \neg \beta}{\alpha}$$

Inference Rules for Prop. Logic

- Resolution

- Most difficult because β cannot be both true and false
- One of the other disjuncts must be true in one of the premises (implication is transitive)

$$\frac{\alpha \vee \beta, \neg \beta \vee \gamma}{\alpha \vee \gamma}$$

Either:

$$\frac{\neg \beta \text{ OR } \beta}{\alpha \vee \beta, \neg \beta} \text{ OR } \frac{\neg \beta \vee \gamma, \beta}{\gamma}$$
$$\alpha \text{ OR } \gamma$$

Monotonicity

- A logic is monotonic if when add new sentences to KB, all sentences entailed by original KB are still entailed by the new larger KB

TASK: Find the Wumpus

Can we infer that the Wumpus is in cell (1,3), given our percepts and environment rules?

A = agent

B = breeze

OK = safe square

S = stench

V = visited

W = wumpus

4			
3			
W!			
2			
OK	S	OK	
	A		
1			
OK	OK	B	PIT
V	V		
1	2	3	4

Wumpus Knowledge Base

- Percept sentences (facts) “at this point”

$\text{``}S_{1,1}\text{''}$ $\text{``}B_{1,1}\text{''}$
 $\text{``}S_{2,1}\text{''}$ $B_{2,1}$
 $S_{1,2}$ $\text{``}B_{1,2}\text{''}$

2	OK S A	
1	OK V	OK B V
	1	2

Environment Rules

$R_I: \text{~~~} S_{I,1} \Rightarrow \text{~~~} W_{I,1} \wedge \text{~~~} W_{I,2} \wedge \text{~~~} W_{2,1}$

3	 W?	
2	OK S A	OK
1	OK	OK
	1	2

Environment Rules

 W?		
OK <input type="checkbox"/> A	S	OK
OK		OK
1	2	3

Environment Rules

 W?		
OK <input type="checkbox"/> A	S	OK
OK		OK
1	2	3

Environment Rules

$$R_4: S_{1,2} \Rightarrow W_{1,3} \vee W_{1,2} \vee W_{2,2} \vee W_{1,1}$$

3	 W?	
2	OK S A	OK
1	OK	OK
	1 2 3	

Conclude $W_{1,3}$?

- Does the Wumpus reside in square (1,3) ?
- In other words, can we infer $W_{1,3}$ from our knowledge base?

$$KB \vdash_i W_{1,3}$$

Conclude $W_{I,3}$ (Step #1)

- Modus Ponens $\frac{\alpha \Rightarrow \beta, \alpha}{\beta}$

$R_I: \text{感知} S_{I,1} \Rightarrow \text{感知} W_{I,1} \wedge \text{感知} W_{I,2} \wedge \text{感知} W_{2,1}$

Percept: $\text{感知} S_{I,1}$

Infer

$\text{感知} W_{I,1} \wedge \text{感知} W_{I,2} \wedge \text{感知} W_{2,1}$

Conclude $W_{I,3}$ (Step #2)

- And-Elimination

$$\frac{\alpha_1 \wedge \alpha_2 \wedge \dots \wedge \alpha_n}{\alpha_i}$$

 $W_{I,1} \wedge$  $W_{I,2} \wedge$  $W_{2,1}$

Infer

 $W_{I,1}$  $W_{I,2}$  $W_{2,1}$

Conclude $W_{1,3}$ (Step #3)

- Modus Ponens
$$\frac{\alpha \Rightarrow \beta, \quad \alpha}{\beta}$$

R_2 : $\neg S_{2,1} \Rightarrow \neg W_{1,1} \wedge \neg W_{2,1} \wedge \neg W_{2,2} \wedge \neg W_{3,1}$

Percept: $\neg S_{2,1}$

Infer

$\neg W_{1,1} \wedge \neg W_{2,1} \wedge \neg W_{2,2} \wedge \neg W_{3,1}$

And-Elimination
$$\frac{\alpha_1 \wedge \alpha_2 \wedge \dots \wedge \alpha_n}{\alpha_i}$$

$\neg W_{1,1} \quad \neg W_{2,1} \quad \neg W_{2,2} \quad \neg W_{3,1}$

Conclude $W_{I,3}$ (Step #4)

- Modus Ponens $\frac{\alpha \Rightarrow \beta, \alpha}{\beta}$

$R_4: S_{I,2} \Rightarrow W_{I,3} \vee W_{I,2} \vee W_{2,2} \vee W_{I,1}$

Percept: $S_{I,2}$

Infer

$W_{I,3} \vee W_{I,2} \vee W_{2,2} \vee W_{I,1}$

Conclude $W_{1,3}$ (Step #5)

- Unit Resolution
$$\frac{\alpha \vee \beta, \neg \beta}{\alpha}$$

$W_{1,3} \vee W_{1,2} \vee W_{2,2} \vee W_{1,1}$ from Step #4

 $W_{1,1}$ from Step #2

Infer

$W_{1,3} \vee W_{1,2} \vee W_{2,2}$

Conclude $W_{1,3}$ (Step #6)

- Unit Resolution
$$\frac{\alpha \vee \beta, \neg \beta}{\alpha}$$

$W_{1,3} \vee W_{1,2} \vee W_{2,2}$ from Step #5

 $W_{2,2}$ from Step #3

Infer

$W_{1,3} \vee W_{1,2}$

Conclude $W_{1,3}$ (Step #7)

- Unit Resolution
$$\frac{\alpha \vee \beta, \neg\beta}{\alpha}$$

$W_{1,3} \vee W_{1,2}$ from Step #6

 $W_{1,2}$ from Step #2

Infer

$W_{1,3} \rightarrow$ The wumpus is in cell 1,3!!!

Wumpus in $W_{1,3}$

3	 W!	
2	OK S A	OK
1	OK	OK
	1	2
		3

Summary

- Propositional logic commits to existence of facts about the world being represented
 - Simple syntax and semantics
- Proof methods
 - Truth table
 - Inference rules
 - Modus Ponens
 - And-Elimination
 - And/Or-Introduction
 - Double-Negation Elimination
 - Unit Resolution
 - Resolution
- Propositional logic quickly becomes impractical